



PRODUCT DATA SHEET

Issue Date: 26.02.11

“FUTURA” LOW PILL FIBRE

“Futura Low Pill” Fibre is based on chemically modified PET and is suitable for textile applications. Futura Low Pill is a low tenacity fibre with low work to break. Fabrics made from Futura Low Pill are free from pilling, soft with comfortable feel, superior drape and aesthetic look. Dye pick up is higher when compared to normal PSF. Futura Low Pill is recommended for premium-blended fabrics especially wool blends.

Features

- Free from pilling
- Softer feel
- Superior drape
- Dyes darker

Specification

Characteristics	Unit	1.5 D	2.5 D	Futura Test Method
Denier	No.	1.5 ± 5%	2.5 ± 5%	FPL – WI – 20-25-08
Tenacity	gpd	3.2 ± 0.2	3.2 ± 0.3	FPL – WI – 20-25-08
Elongation	%	50 ± 5	50 ± 5	FPL – WI – 20-25-08
Finish	%	0.18 ± 0.02	0.20 ± 0.02	FPL – WI – 20-25-02
Crimps	No./Inch	11 ± 1	11 ± 1	FPL – WI – 20-25-06

Denier: 1.5, 2.0, 2.5 and 3.0 denier

Cut length: 38, 44, 51, 60, 64, 76, 89 and 102 mm.

Lustre: Semi-dull and dope dyed.

Applications:

- o Apparels
- o Shirting & Suiting
- o Sarees & Dress materials
- o Premium blends
- o Knitted garments

PACKING:

Bale Wrapper:	Woven HDPE/PP with inner PE liner.
Bale Dimensions:	1120 x 700 x 1070 mm.
Net Weight per bale:	320 – 350 Kgs
Quantity in 1 x 40' FCL:	25000 kg. approx.

Safety Aspects:

- Please refer the MSDS of Futura Polyester Staple Fibre / Tow

b) Handling & StorageHandling (Personnel):

Avoid breathing hot vapors, oil mists and airborne fibres, wash thoroughly after handling.

Personal Precautionary Measures:

No special precautionary measures should be needed under anticipated conditions of use

Storage:

Store cartons and bales in accordance with good material handling practices.

c) Prevention of Fire and Explosion

Keep away from contact with oxidizing materials. Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

Contact Address:

FUTURA FIBRES

A division of FUTURA POLYESTERS LIMITED Tel: 91 44 2594 1313 - 17

1-A Kamarajar Salai,

Fax: 91 44 2594 1566, 1054

Manali, Chennai - 600 068

E-mail: <futurach@fudurapolyesters.com>

India

Website: www.fudurapolyesters.com

All Products are under continual improvement. Right is reserved to modify product/process without prior notice subject to performance criteria as per Product Data Sheet.